VALENTE SINCE 1919 SPA
One hundred years of reliability

Headquarters:
Via Don Minzoni, 6
20045 – Lainate (MI) Italy
Tel. +39 02.93799212 - Fax. +39 02. 93799349
mail@valente.it
www.valente.it www.valente1919.com

Registered office:
Via Emilio Motta, 6
20144 – Milano (MI) Italy
info@valente.it

ISO 9001:2015 Certified

FASTENING SYSTEM FOR CRANE RAILS VALEX 4023

RAIL WITHOUT PAD

RAIL WITH PAD



RAIL WITHOUT PAD

RAIL WITH PAD



FEATURES

- System made up of one clip one bolt and nut.
- Possibility of lateral adjustment.
- Easy and simple installation.
- Easy and simple maintenance.



COMPONENTS

- CLIP

APPLICATIONS

VALEX 4023 is a direct fastening system specifically developed for crane rails, however, it can also be used for train and light (Decauville) rails, with very positive results.
A very rugged, reliable system of contained dimensions, which can be used with every type of crane, independently of the driving system.



Dimensions [mm]	E	F	G	H	L	L1	L2	M	N	O	P	Weight [g]
VALEX 4023	-	23	50	-	-	23	35	22	52	90	70	750

VALEX 4023 CLIP

VALENTE SPA SINCE 1919
One hundred years of reliability

Headquarters:
Via Don Minzoni, 6
20045 – Lainate (MI) Italy
Tel. +39 02.93799212 - Fax. +39 02. 93799349
mail@valente.it
www.valente.it www.valente1919.com

Registered office:
Via Emilio Motta, 6
20144 – Milano (MI) Italy
info@valente.it

ISO 9001:2015 Certified

FASTENING SYSTEM FOR CRANE RAILS VALEX 4023

RAIL TYPE	A [mm]	B [mm]	C [mm]	Weight [kg/m]	WITH PAD	WITHOUT PAD
A 45	45,00	55,00	125,00	22,10	-	VALEX 4023
A 55	55,00	65,00	150,00	31,80	-	VALEX 4023
A 65	65,00	75,00	175,00	43,10	-	VALEX 4023
A 75	75,00	85,00	200,00	56,20	-	VALEX 4023
A 100	100,00	95,00	200,00	74,30	-	VALEX 4023
A 120	120,00	105,00	220,00	100,00	-	-
A 150	150,00	150,00	220,00	150,30	-	-
CR 104	63,50	127,00	127,00	51,59	-	-
CR 105	65,10	131,80	131,80	52,09	-	-
CR 135	76,20	146,00	131,80	66,97	-	-
CR 171	101,60	152,40	152,40	84,83	-	-
MRS 87 A	101,60	152,40	152,40	86,80	-	-
CR 175	102,40	152,40	152,40	86,80	-	-
MRS 125	120,00	180,00	180,00	125,00	-	-
S 7	25,00	65,00	50,00	6,75	-	-
S 10	32,00	70,00	58,00	10,00	-	-
S 14	38,00	80,00	70,00	14,00	-	-
S 18	43,00	93,00	82,00	18,30	-	-
S 20	44,00	100,00	82,00	19,80	-	-
S 24	53,00	115,00	90,00	24,43	-	-
25 kg/m	50,00	115,00	90,00	25,00	-	-
S 26 (AFNOR 26)	50,00	110,00	100,00	26,27	-	VALEX 4023
27 E1 (27 UNI)	50,00	120,00	95,00	27,06	-	-
AFNOR 30	56,00	125,50	106,00	29,98	-	VALEX 4023
30 E1 (S 30)	60,30	108,00	108,00	30,13	-	VALEX 4023
33 E1 (S 33)	58,00	134,00	105,00	33,47	-	VALEX 4023
36 E1 (36 UNI)	60,00	130,00	100,00	36,26	-	-
40 E1 (S 41-R14)	67,00	138,00	125,00	40,95	-	VALEX 4023
46 E4 (46 UNI)	65,00	145,00	135,00	46,90	-	-
49 E1 (S 49)	67,00	149,00	125,00	49,39	-	-
50 E5 (50 UNI)	67,00	148,00	135,00	49,90	-	-
54 E1 (UIC 54)	70,00	159,00	140,00	54,77	-	-
60 E1 (UIC 60)	72,00	172,00	150,00	60,21	-	-

Valex fastening systems can also be used for several other rail profiles, not listed. A complete range of compatible rails is available on request.

GENERAL INSTRUCTIONS

The selection of the fastening system, either for crane, train, or light (Decauville) rails, is a critically important decision both when placing a track or a single rail. The wrong selection could have expensive consequences and create serious problems such as:

- Slow down or shut down of the production process
- Excessive and, or irregular wear of the rails
- Damage of the mechanical components of the crane
- Damage of the supporting base
- Damage of the fastening systems

Valex fastening systems were developed through experience accumulated over more than 100 years of activity.

Valex fastening systems offer a wide range of alternatives, which would perform in the most effective and efficient way in every possible situation.

FIXING DETAILS



INSTALLATION INSTRUCTIONS

- Carefully align the rails.
- Place the clips in direct contact with the rails.
- Position the washer and insert the screw.
- Perform an initial light tightening.
- Complete the tightening process according to recommended torque.

TECHNICAL SPECIFICATIONS

- Side load 70 KN
- Lateral adjustament 8 mm
- Torque tightening 320 Nm
- Bolt 8.8 gr M20 – NOT INCLUDED
- Steel quality S275JR

VALENTE S.p.A. aims to provide maximum assistance and total customer satisfaction, guarantees the origin and quality of its products, and supplies any reasonably requested documentation.

VALENTE S.p.A. reserves the right to modify the information contained in the technical data sheet without notice and disclaims any responsibility for any inaccuracies or changes in the reported data.